

What is Claimed is:

1. An electrical contact, comprising:
a rear end having a first interface; and
a front end having a second interface to a connector, wherein the second interface prevents a flexible contact medium on the electrical contact from being distorted by the connector.
2. The electrical contact of claim 1, wherein the first interface connects to a connection medium.
3. The electrical contact of claim 1, wherein a front end of the flexible contact medium is isolated from the connector by a flange on the second interface.
4. The electrical contact of claim 3, wherein the flange is a part of a first insulator.
5. The electrical contact of claim 1, wherein a front end of the flexible contact medium is tapered toward an outer boundary of the second interface.
6. The electrical contact of claim 1, wherein a front end of the flexible contact medium is isolated from the connector by a curved rim on the second interface.

7. The electrical contact of claim 1, wherein the second interface permits connection of the connector with a rear portion of the flexible contact medium.
8. The electrical contact of claim 1, wherein the second interface guides the connector.
9. The electrical contact of claim 1, wherein the connector is a triaxial connector.
10. The electrical contact of claim 1, wherein the electrical contact is a male triaxial pin contact.
11. The electrical contact of claim 1, wherein the rear end is tubular.
12. The electrical contact of claim 1, wherein the front end is tubular.
13. The electrical contact of claim 1, wherein the first interface has one or more connection pins.
14. The electrical contact of claim 13, wherein the connection pins include at least one of the following: a center pin, an intermediate pin, and an outer pin.
15. An electrical contact, comprising:
an intermediate contact having a flexible connection medium;

an outer contact surrounding the intermediate contact;

a first insulator surrounding the intermediate contact and the flexible connection medium, wherein the first insulator provides electrical isolation of the intermediate contact from the outer contact, and wherein the first insulator has a front face that protects the flexible connection medium from being distorted by an electrical connector, and wherein the outer contact surrounds the first insulator; and

a center contact surrounded by the intermediate contact.

16. The electrical contact of claim 15, further comprising a second insulator located between the intermediate contact and the center contact, wherein the second insulator provides electrical isolation of the center contact from the intermediate contact.

17. The electrical contact of claim 15, further comprising a flange on the front face, wherein the flange isolates a front portion of the flexible connection medium from the mating connector.

18. The electrical contact of claim 15, further comprising a ledge on the front face, wherein a front portion of the flexible connection medium is located below the ledge.

19. The electrical contact of claim 15, wherein a front portion of the flexible connection medium has a taper, and wherein the taper guides the mating connector within the flexible connection medium.

20. The electrical contact of claim 15, wherein a front portion of the flexible contact medium is tapered toward an outer boundary of the second interface.
21. The electrical contact of claim 15, wherein a front portion of the flexible contact medium is isolated from the connector by a curved rim on the second interface.
22. The electrical contact of claim 15, wherein the second interface permits connection of the connector with a rear portion of the flexible contact medium.
23. The electrical contact of claim 15, further comprising a third insulator surrounding the center contact, wherein the third insulator provides electrical isolation of the center contact.
24. The electrical contact of claim 15, wherein the center contact is connected to a center pin that extends from a rear side of the outer contact such that the center contact is within a plane of the outer contact.
25. The electrical contact of claim 24, wherein the center pin carries a signal.

26. The electrical contact of claim 15, wherein the intermediate contact is connected to an intermediate pin that extends from a rear side of the outer contact such that the center contact is within a plane of the outer contact.

27. The electrical contact of claim 26, wherein the intermediate pin carries a ground potential.

28. The electrical contact of claim 26, wherein the intermediate pin carries a signal.

29. The electrical contact of claim 15, wherein the outer contact is connected to outer pin that extends from a rear side of the outer contact such that the center contact is within a boundary of the outer contact.

30. The electrical contact of claim 29, wherein the outer pin carries a ground potential.

31. An electrical connector, comprising:

a shell;

an electrical contact located within the housing, comprising:

a rear end having a first interface, and

a front end having a second interface to a connector, wherein the

second interface prevents the electrical contact from being distorted by the connector; and

at least one other electrical contact located within the shell.

32. The electrical connector of claim 31, wherein the shell is substantially circular and surrounds the electrical contacts.
33. An insulator device for a flexible contact medium, comprising:
- a front end having a front opening; and
 - a rear end having a rear opening, wherein the rear opening is larger than the front opening, and wherein the front opening protects the flexible contact medium from being distorted by a mating connector entering the front opening.
34. The insulator device of claim 33, wherein the front opening has a tapered end smaller than the flexible contact medium.
35. The insulator device of claim 33, wherein the front opening receives a connector.
36. The insulator device of claim 33, wherein the rear opening receives the flexible contact medium.
37. The insulator device of claim 33, wherein the insulator device is a part of a male triaxial electrical connector.

38. The insulator device of claim 33, wherein the insulator device is surrounded by an outer contact.

39. The insulator device of claim 33, wherein the flexible contact medium is an intermediate contact that surrounds a center contact.

40. A pin contact, comprising:

an outer contact;

an intermediate contact surrounded by the outer contact, wherein the intermediate contact has an outer insulative body and an inner flexible conductive body, and wherein the outer insulative body prevents the inner flexible conductive body from being distorted by a connector mating with the pin contact; and

a center contact surrounded by the outer contact and the intermediate contact.

41. The pin contact in claim 40, further comprising a second insulator located between the intermediate contact and the center contact, wherein the second insulator provides electrical isolation of the center contact from the intermediate contact.

42. The pin contact in claim 40, further comprising a third insulator surrounding the center contact, wherein the third insulator provides electrical isolation of the center contact.

43. The pin contact in claim 40, wherein the center contact is connected to a center pin that extends from a rear side of the outer contact such that the center contact is within a plane of the outer contact.

110
112
114
116
118
120
122
124
126
128
130
132
134
136
138
140
142
144
146
148
150
152
154
156
158
160
162
164
166
168
170
172
174
176
178
180
182
184
186
188
190
192
194
196
198
200
202
204
206
208
210
212
214
216
218
220
222
224
226
228
230
232
234
236
238
240
242
244
246
248
250
252
254
256
258
260
262
264
266
268
270
272
274
276
278
280
282
284
286
288
290
292
294
296
298
300
302
304
306
308
310
312
314
316
318
320
322
324
326
328
330
332
334
336
338
340
342
344
346
348
350
352
354
356
358
360
362
364
366
368
370
372
374
376
378
380
382
384
386
388
390
392
394
396
398
400
402
404
406
408
410
412
414
416
418
420
422
424
426
428
430
432
434
436
438
440
442
444
446
448
450
452
454
456
458
460
462
464
466
468
470
472
474
476
478
480
482
484
486
488
490
492
494
496
498
500
502
504
506
508
510
512
514
516
518
520
522
524
526
528
530
532
534
536
538
540
542
544
546
548
550
552
554
556
558
560
562
564
566
568
570
572
574
576
578
580
582
584
586
588
590
592
594
596
598
600
602
604
606
608
610
612
614
616
618
620
622
624
626
628
630
632
634
636
638
640
642
644
646
648
650
652
654
656
658
660
662
664
666
668
670
672
674
676
678
680
682
684
686
688
690
692
694
696
698
700
702
704
706
708
710
712
714
716
718
720
722
724
726
728
730
732
734
736
738
740
742
744
746
748
750
752
754
756
758
760
762
764
766
768
770
772
774
776
778
780
782
784
786
788
790
792
794
796
798
800
802
804
806
808
810
812
814
816
818
820
822
824
826
828
830
832
834
836
838
840
842
844
846
848
850
852
854
856
858
860
862
864
866
868
870
872
874
876
878
880
882
884
886
888
890
892
894
896
898
900
902
904
906
908
910
912
914
916
918
920
922
924
926
928
930
932
934
936
938
940
942
944
946
948
950
952
954
956
958
960
962
964
966
968
970
972
974
976
978
980
982
984
986
988
990
992
994
996
998
1000